


Simple, Reliable and Accurate

- Completely Automatic Operation
- Easy Adjustment and Maintenance
- Quality Approved Materials
- World Wide Support





CLA-VAL 81-01 Typical Application

The CLA-VAL 81-01 is designed to be used when a positive shut-off is required.

The CLA-VAL 81-01 is typically installed on the discharge of pumps or well pumping systems to prevent backflow when the pump is off.

Installation: Reverse Flow



The CLA-VAL SERIES 81 is a hydraulically operated Check Valve. The valve opens when inlet pressure exceeds outlet pressure. In case of reversal pressure, the higher outlet pressure closes the valve to prevent backflow through the valve.

Make your valve even Better!

LFS Option?	Control Low flows or night flows
KO Option?	Extend valve life with Anti-Cavitation trim
KG1 Option?	Use stem cleaning for harsh water
Maintenance?	Check on periodic maintenance
Environment?	Adapt to high temperatures or frost risk
Security?	Add hydraulic safety back-up to your valve
Protection?	<u>Remove</u> excessive system overpressures
Corrosion?	Protect your valve with upgraded materials
Not just Products but Solutions: contact CLA-VAL!	



© Copyright CLA-VAL Europe - Specifications subject to change without notice - no contractual illustrations.