



### STANDARD EQUIPMENT

No	Description	Qty	Type
1	MAIN VALVE HYTROL AE/GE/NGE	1	100-01
2	ISOLATION BALL VALVE	3	RB-117
3	STRAINER WITH INCORPORATED ORIFICE	1	X44-A
4A	ONE-WAY FLOW CONTROL (OPENING SPEED)	1	CV
4B	ONE-WAY FLOW CONTROL (CLOSING SPEED)	1	CV
5	POSITIONING MOTORIZED PRESSURE REDUCING CONTROL	1	CRD-34
6	ELECTRONIC ADVANCED CONTROLLER	1	D22
7	INSERTION FLOWMETER	1	e-Flowmeter

### OPTIONAL FEATURES

No	Description	Qty	Type
P9	PRESSURE REDUCING CONTROL	1	CRD + RB-117

### NOTES

AE/GE : DN 32 - DN 400 / NGE : DN 50 - DN 600  
 RB-117 (2D), (2E), (2F), (2G) if option (P9)  
 Recommended ValvApps: D22-POUT-DRV.01  
 Standard wiring schematic: D22-17-0001

OPTIONAL FEATURES : \_\_\_\_\_  
 NOT FURNISHED BY CLA-VAL : \_\_\_\_\_